

	NCF 30/15	NCF 120/15	NCF 30/25	NCF 40/25	NCF 50/25	NCF 80/20	NCF 120/25	NCF 160/25
Capacity:	1100–4400 m ³ /h	5700–14400 m ³ /h	1700–6500 m ³ /h	2000–6700 m ³ /h	1800–5900 m ³ /h	2300–9100 m ³ /h	3500–12400 m ³ /h	4600–17900 m ³ /h
Total pressure:	1840–700 Pa	2520–740 Pa	2440–920 Pa	3440–1410 Pa	4550–1690 Pa	3070–1150 Pa	4500–2000 Pa	5030–1880 Pa
Motor power:	2,2 kW	7,5 kW	4 kW	5,5 kW	5,5 kW	7,5 kW	15 kW	18,5 kW
Speed:	2880 rpm	2930 rpm	2905 rpm	2925 rpm	2925 rpm	2930 rpm	2940 rpm	2940 rpm
Part no:	14550128	14550928	14551028	14551128	14551228	14551328	14551428	14551528
Voltage:	3~, 230Δ / 400Y V	3~, 400Δ / 690Y V	3~, 400Δ / 690Y V	3~, 400Δ / 690Y V	3~, 400Δ / 690Y V	3~, 400Δ / 690Y V	3~, 400Δ / 690Y V	3~, 400Δ / 690Y V
Current at rated voltage:	7,9 / 4,55 A	13,8 / 8,0 A	7,8 / 4,5 A	10,3 / 6,0 A	10,3 / 6,0 A	13,8 / 8,0 A	26,5 / 15,3 A	32,5 / 18,8 A
Frequency:	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
Degree of protection:	IP 55	IP 55	IP 55	IP 55	IP 55	IP 55	IP 55	IP 55
Motor Energy class	IE3	IE3	IE3	IE3	IE3	IE3	IE3	IE3
Weight:	67 kg	123 kg	105 kg	110 kg	112 kg	150 kg	232 kg	292 kg
Working temperature:	Maximum +60°C	Maximum +60°C	Maximum +60°C	Maximum +60°C	Maximum +60°C	Maximum +60°C	Maximum +60°C	Maximum +60°C
Ambient temperature:	-30°C to +40°C	-30°C to +40°C	-30°C to +40°C	-30°C to +40°C	-30°C to +40°C	-30°C to +40°C	-30°C to +40°C	-30°C to +40°C